

Grinding disc

A 24 R SUPRA



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□□
Aggression	■■■■■□□□
Service life	■■■■■□□□

Product benefit

With optimized recipe for use on steel - Also suitable for use on stainless steel - Large product range

Application

Steel	●
Stainless steel	◐
Castings	◑

Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop

Diameter x Thickness x Bore	Form	Vmax m/s	Max. RPM	Article number
4 x 1/4 x 5/8		80 m/s	15300 rpm	6578
4-1/2 x 1/4 x 7/8		80 m/s	13300 rpm	13401
5 x 1/4 x 7/8		80 m/s	12200 rpm	13402
6 x 1/4 x 7/8		80 m/s	10200 rpm	13403
7 x 3/8 x 7/8		80 m/s	8500 rpm	13423
7 x 1/4 x 7/8		80 m/s	8500 rpm	13413
7 x 5/16 x 7/8		80 m/s	8500 rpm	13418
9 x 3/16 x 7/8		80 m/s	6600 rpm	13428
9 x 1/4 x 7/8		80 m/s	6600 rpm	13433

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

