

# Cut-off wheel

# A 24 R SUPRA



## Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□
Aggression	■■■■□□□
Service life	■■■■■□□

## Product benefit

Optimized combination for use on steel - Can be used on stainless steel - Good cutting properties

## Application

Steel	●
Stainless steel	◐
Castings	◑

## Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop

Diameter x Thickness x Bore	Form	Vmax m/s	Max. RPM	Article number
4 x 3/32 x 5/8		80 m/s	15300 rpm	13754
4-1/2 x 3/32 x 7/8		80 m/s	13300 rpm	13466
5 x 3/32 x 7/8		80 m/s	12200 rpm	13295
5 x 3/32 x 7/8		80 m/s	12200 rpm	13738
7 x 1/8 x 7/8		80 m/s	8500 rpm	13470
7 x 9/64 x 7/8		80 m/s	8500 rpm	13474
9 x 1/8 x 7/8		80 m/s	6600 rpm	13478

**Klingspor Schleifsysteme GmbH und Co. KG**

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

